

BASE PLATE TWO POST LIFT

This is the basic model of base plate two post lift with asymmetric or symmetric arm design.

With an option of pneumatic safety lock release.



FEATURES

- Lifting height reaches 1900mm with load
- Minimum height as low as 100mm
- Limitation switch included.
- Pull two sides of safety release cable to lower the vehicle
- Symmetric and Asymmetric arm configuration
- Dual cylinder structure, chain lifting system with wire rope for synchronization
- 24V voltage operation system
- Chain protectors and foot protectors included
- 3 sets of height adapters included
- Step by step installation Instructions included with each unit

SPECIFICATIONS

MODEL NO	HCT2.5L30	HCT2.5AL30	HCT2.5L40	HCT2.5AL40
Lifting capacity	3.2 T	3.2 T	4.0 T	4.0 T
Lifting height	1900 mm	1900 mm	1900 mm	1900 mm
Min. height	100 mm	100 mm	100 mm	100 mm
Overall height	2826 mm	2826 mm	2826 mm	2826 mm
Between columns	2860 mm	2860 mm	2860 mm	2860 mm
Lifting time	50 S	50 S	50 S	50 S
Motor power	2.2 KW	2.2 KW	2.2 KW	2.2 KW
Power supply	220/380 V, 50/60 HZ	220/380 V, 50/60 HZ	220/380 V, 50/60 HZ	220/380 V, 50/60 HZ
Weight	630 kg	630 kg	680 kg	680 kg
Asymmetric arms	No	Yes	No	Yes
Symmetric arms	Yes	No	Yes	No

