Brake Disk Lathe

Features

Provide variable speed and rotation torque during brake machining is a characteristic of this equipment.
©☐The spindle rotation speed swivels within a certain range,this can eliminate the mechanical resonance and enable the machined surface to be smooth.
©☐The 1.5-hp powerful motor can machine brakes for4-wheel drive automobiles,1t trucks and even medium duty truck's rear wheels easily.
©☐The micro-round cutter blade can undergo knock,it can be rotated by an angle after it has been worn to elongate its service life.
©☐The brake lathe can be rotated180¡ã to machine the automobile at its another side. It is very convenientin use because it is unnecessary to remove the bolts and move the arbor.
©☐Theunique twin-arbor design makes it be adjusted conveniently and the machining with high efficiency.
©☐Semiautomatic operation system.
©☐Automatic safety and shutdown system.
©☐Fast connection system.
©☐Intermittent feed mechanism makes the machined surface conform to be the demands of use

Main specifications

Model	OTCL450A
Max. rotor turning Dia.	360mm
Max. rotor thickness	51mm
Max. rotor friction surface area	76mm
Feed distance	110mm
Spindle revolutions	30-120rpm
Motor power	3450rpm 1.1kW 1.5Hp
N.W.	41kgs without trolley
Electric power	AC220v 50/60Hz 15A